



1001166 461



1001172 461

DOLIX OUT
EL, round, QPAR51

E-A++ Spektrum A++-E




Produktangaben

220-240V ~50/60Hz
Material: Aluminium / Glas

IP 65 0,17 0,2 IK02

Maßzeichnung



Hinweis

Materialstärke Einbaufäche: 20 mm max

Leuchtmittlempfehlung

LED GU10 5,5W 38°
2700K 400lm EEK=A+
6kWh/1000h

Art. Nr. 1001030

LED GU10 7,2W 36°
3000K 520lm EEK=A+
8kWh/1000h

Art. Nr. 1001562

Leuchtmittelangaben

max. 50W QPAR51

Variante	Art. Nr.
GU10 QPAR51 □ weiß	1001165
GU10 QPAR51 ■ chrom	1001166
GU10 QPAR51 ■ grau / transparent	1001167
GU10 QPAR51 ■ chrom	1001168

DOLIX OUT
EL, square, QPAR51

E-A++ Spektrum A++-E




Produktangaben

220-240V ~50/60Hz
Material: Aluminium / Glas

IP 65 0,19 0,2 IK02

Maßzeichnung



Hinweis

Materialstärke Einbaufäche: 20 mm max

Leuchtmittlempfehlung

LED GU10 5,5W 38°
2700K 400lm EEK=A+
6kWh/1000h

Art. Nr. 1001030

LED GU10 7,2W 36°
3000K 520lm EEK=A+
8kWh/1000h

Art. Nr. 1001562

Leuchtmittelangaben

max. 50W QPAR51

Variante	Art. Nr.
GU10 QPAR51 □ weiß	1001169
GU10 QPAR51 ■ chrom	1001170
GU10 QPAR51 ■ grau / transparent	1001171
GU10 QPAR51 ■ chrom	1001172