



143440 515



143430 515

BIMA
1Ph., single, QPAR51



SOCKET
INSIDE




Produktangaben

220-240V ~50/60Hz
Material: Aluminium



Maßzeichnung



Leuchtmittlempfehlung

LED GU10 6W 36°
3000K 460lm
6kWh/1000h
Art. Nr. 1005080



LED GU10 5,5W 38°
2700K 400lm
6kWh/1000h
Art. Nr. 1001030



Leuchtmittelangaben

max. 50W QPAR51
Ø: 5 cm max. L: 5,7 cm max.

Variante	Art. Nr.
GU10 QPAR51	
■ schwarz	143440
□ weiß	143441
■ grau	143442

BIMA
1Ph., double, QPAR51



SOCKET
INSIDE




Produktangaben

220-240V ~50/60Hz
Material: Aluminium



Maßzeichnung



Leuchtmittlempfehlung

LED GU10 6W 36°
3000K 460lm
6kWh/1000h
Art. Nr. 1005080



LED GU10 6W 36°
4000K 460lm
6kWh/1000h
Art. Nr. 1005083



Leuchtmittelangaben

2x max. 50W QPAR51
Ø: 5 cm max. L: 5,7 cm max.

Variante	Art. Nr.
GU10 QPAR51	
■ schwarz	143430
□ weiß	143431
■ grau	143432