



184450 535



184440 535

BIMA
EASYTEC® II, single, QPAR51



SOCKET
INSIDE



BIMA 2
EASYTEC® II, double, QPAR51



SOCKET
INSIDE



Produktangaben

220-240V ~50/60Hz
Material: Aluminium



0,3 350° 180°


Produktangaben

220-240V ~50/60Hz
Material: Aluminium




0,5 350° 180°

Maßzeichnung



Maßzeichnung



Leuchtmittlempfehlung

LED GU10 6W 36°
3000K 460lm
6kWh/1000h
Art. Nr. 1005080



LED GU10 5,5W 38°
2700K 400lm
6kWh/1000h
Art. Nr. 1001030



Leuchtmittlempfehlung

LED GU10 6W 36°
3000K 460lm
6kWh/1000h
Art. Nr. 1005078



LED GU10 6W 36°
4000K 460lm
6kWh/1000h
Art. Nr. 1005081



Leuchtmittelangaben

max. 50W QPAR51
Ø: 5,1 cm max. L: 5,7 cm max.

Leuchtmittelangaben

2x max. 50W QPAR51
Ø: 5,1 cm max. L: 5,7 cm max.

Variante	Art. Nr.
GU10 QPAR51	
■ schwarz	184450
GU10 QPAR51	
■ grau	184452

Variante	Art. Nr.
GU10 QPAR51	
■ schwarz	184440